



Style MTA2 Plug Termination (Stock)



Ordering a Stock MTA2 Thermocouple

(Thermocouples not available from stock can be custom manufactured—see page 14-17)

TEMPCO stocks **MTA2 style Thermocouples** in type J and K in the standard lengths listed in the following two tables. These thermocouples have a standard Male Plug Termination.

Order a stock unit from the tables after completing the ordering code with the Junction Type Code from Box 4 and Optional Compression Fitting Code from Box 5 below.

Type J – 316 SS Sheath

Diameter	"L" Dimension			
	6"	12"	18"	24"
0.063"	ST2-JD06 <input type="checkbox"/>	ST2-JD12 <input type="checkbox"/>	ST2-JD18 <input type="checkbox"/>	ST2-JD24 <input type="checkbox"/>
0.125"	ST2-JF06 <input type="checkbox"/>	ST2-JF12 <input type="checkbox"/>	ST2-JF18 <input type="checkbox"/>	ST2-JF24 <input type="checkbox"/>

Type K – Alloy 600 Sheath

Diameter	"L" Dimension			
	6"	12"	18"	24"
0.063"	ST2-KD06 <input type="checkbox"/>	ST2-KD12 <input type="checkbox"/>	ST2-KD18 <input type="checkbox"/>	ST2-KD24 <input type="checkbox"/>
0.125"	ST2-KF06 <input type="checkbox"/>	ST2-KF12 <input type="checkbox"/>	ST2-KF18 <input type="checkbox"/>	ST2-KF24 <input type="checkbox"/>

Stock Modification for Fast Delivery

Above stocked items can be cut to desired length and junctioned for fast delivery. To order a probe length not listed in the tables above, complete the Code Number below.

Ordering Code: **ST2** -

Calibration BOX 1
ANSI Standard Tolerances **J K**

"L" Dimension BOX 3
06", 12", 18", 24" Stock Lengths
For other lengths specify in inches.

Optional Compression Fitting BOX 5
1 = 1/8" NPT SS **4** = 1/8" NPT Brass
2 = 1/4" NPT SS **5** = 1/4" NPT Brass
3 = 1/2" NPT SS **6** = 1/2" NPT Brass
0 = None Required

Diameter BOX 2
D = .063"
F = .125"

Junction BOX 4
G = Grounded
U = Ungrounded
E = Exposed



Optional Installation Compression Fitting
See Box 5

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.