Tempco-Pak Heaters



Standard (Non-Stock) Square Straight Tempco-Pak Cable Heaters

Part Numbers are for heaters with 48" plain leads.

Longer lead length as well as optional stainless steel wire braid (B), fiberglass sleeve (S), stainless steel armored cable (A) or galvanized armored cable (C) protection is available upon request. See ordering code worksheet below for lead wire protection and lead length desired.

Standard Tempco-Pak Heaters are made with 304 Stainless Steel Sheath.

Cable	Sheath Length		Cold Length			Watt Density			"J" T/C	Part
Cross Section	in	mm	in	mm	Watts	W/in²	W/cm ²	Volts	Junction	Number
	141/8	359	2	51	250	41.2	6.39	240	UG-T	MHS00128
	181/4	464	13/4	44	250	30.3	4.70	240	UG-T	MHS00129
	221/8	581	21/8	54	250	24.0	3.72	240	GRD	MHS00121
	231/4	591	1½	38	450	41.3	6.40	240	UG-M	MHS00122
.125" x .125"	26	660	4	101	300	27.2	4.22	240	GRD	MHS00123
(Square)	29	737	1½	38	450	32.7	5.06	240	UG-N	MHS00124
	36%	936	2	51	300	17.2	2.66	240	GRD	MHS00125
	411/8	1045	1%	47	300	15.2	2.35	240	UG-M	MHS00126
	43 1/8	1108	1%	47	300	14.3	2.21	240	UG-M	MHS00127
	20	508	2½	64	315	36.0	5.58	240	N/A	HHS00167
	31½	800	2½	64	315	21.7	3.36	240	N/A	HHS00168
	31¾	806	2½	64	600	41.0	6.36	240	N/A	HHS00169

(UG-M) — Ungrounded T/C junction is at the middle of the hot section

(UG-T) — Ungrounded T/C junction is at the tip

(UG-N) — Ungrounded T/C junction is 7" from the tip

Lead Wire Abrasion Protection Terminations

Type A - Stainless Steel Armor Cable



Type C__ - Galvanized Armor Cable





NOTE: Complete termination descriptions are on page 5-5.

Stainless Steel Overbraid



Type S__ - Fiberglass Sleeve



Potting Adapter Size without Crimping

5/16" O.D. × 1-1/2" long

Ordering Code:



Ordering Information

Part Numbers above are for Square Rectangular Tempco-Pak heaters with 48" plain lead wires. If you need other than standard 48" leads and/or wire protection use the ordering codes at the right and a part number will be assigned.

Lead Length BOX 1 Whole inches 000 to 999 **Termination Type** BOX 2

A = Stn. Stl. Cable

 $\mathbf{B} = \operatorname{Stn. Stl. Wire Braid}$

C = Galvanized Cable

S = Fiberglass Sleeve

M = Plain Leads (Do not fill Box 3)

★ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Length of Protection BOX 3 Whole inches 000 to 999

View Product Inventory @ www.tempco.com